



Technical Details

HG SUPER COMPACT SERIES, 60Hz		HG 3.7	HG 6	HG 8	HG 14	HG 18	HG 30
Output characteristics							
Output power max.	kW	3,7	6	8	14	18	30
Power factor / power	cos φ/kW	1,0/3,7	1,0/6,0	1,0/8,0	1,0/14	1,0/18	1,0/30
Output Voltages, VAC	1 phase	120	120	120	120	120	120
	1 phase	–	–	240	240	240	240
Nominal Current, A□	120V	30	22.5X2	33.3	58,3	75	125
	240V	–	–	16.6X2	29,2x2	37,5x2	60
Sockets (120V / 240V / cable K)		2 / - / -	3 / - / -	2 / 1 / -	4 / 1 / -	4 / - / -	- / - / k
Hydraulic power requirements							
Flow min.	U.S. gpm (1 / min)	5.3 (20)	8.5 (32)	11.4 (43)	15.9 (60)	25.6 (97)	33.0 (125)
Pressure max.	psi (bar)	3100 (210)	3100 (210)	3100 (210)	3100 (210)	4000 (280)	3900 (270)
Overall dimensions							
Length	in (mm)	16.5 (419)	19.3 (490)	21.5 (546)	25.4 (645)	29.2 (742)	29.3 (744)
Width	in (mm)	8.6 (218)	8.3 (211)	8.2 (211)	11.6 (295)	19 (483)	12.8 (325)
Height	in (mm)	8.4 (213)	14.2 (316)	15 (381)	17.5 (445)	12.7 (323)	14.8 (376)
Weight	lbs (kg)	51 (23)	92 (42)	115 (52)	232 (105)	295 (134)	291 (132)